

Wi-Fi Video Doorbell Security Cam with Indoor Chime Bundle Set PC-ABS housing, Silver Edition



ROHS
COMPLIANT



Technical Data

General	
Housing	Polycarbonate - acrylonitrile butadiene styrene, all weather, UV - resistant
Doorbell Button	Touch Button
Mounting Type	Surface - mounted
Approvals	CE - EMC, CE - LVD, FCC, IC - ID, R & TTE, UL, RoHS
Power Supply and Consumption	Existing doorbell wiring or to a 9 - 24 Volts AC/DC power supply; 5 Watts (2.8 Watts without Infrared lamp)
Mounting Type	Surface - mounted
Weight	3.5 oz./ 100 g
Package Weight	2 lbs./ 0.9 kg
Dimensions	D x W x L 22.3mm x 73mm x 85.13mm/ 0.87in x 2.9in x 3.3in
Operating Conditions	-25°C ~ 50°C/ -15°F ~ 125°F
Connectors	Power, Electric/Magnetic door opener/strike, Door chime, Door opener button, Network
Ingress Protection	IP56
Frame color	Silver (Plating) / Silver (Paint) / Black / White
Including Accessories	Power Adaptor, Screwdriver, Screws & Anchors, Drill bit, Wedge Bracket

Video	
Video Resolution	Adjustable: 1280 x 720 (HD) , 640 x 360 (SD) , Auto (default HD)
Picture	720P maximum output 15fps, maximum bit rate 2Mbps
Lens	f 1.3mm, F2.5, horizontal viewing angle of 185°
Infrared Night Vision	Build - in photodiode. 4 build - in Ø5 850nm 14um infrared lamp
Audio	
Audio components	Speakers and microphone, Echo and Noise Canceller
Audio Streaming	Two-way
Network	
Wi-Fi	802.11a/b/g/n 2.4GHz
Motion Sensor	
Type	Passive Infrared sensor (PIR)
Detector angle	185°
Range	10 - 15m (dep. on envirom.)
Integrated Wireless Modules	
Wi-Fi	802.11 a/b/g/n @ 2.4 GHz
Current System requirement	
Mobile device	Phone or tablet with IOS 8 or later, or android 4.1 or
Internet	802.11 a/b/g/n @ 2.4 GHz
Recommended installation height	45 in/115 cm